

## Cook 'n' Hold Ovens

### Low temperature radiant Cook 'n' Hold Oven

#### FEATURES:

- Choice of controls - standard machine is fitted with core probe with digital temperature readout as an optional extra they can also be supplied with an electronic programmable controller with 10 pre-set menus
- Fully insulated Cook-N-Hold gentle radiant oven designed for flavorful results by slow cooking.
- Slow cooking means 15% to 20% less shrinkage.
- Efficient power unit allows for reheating of prepared meals or bulk items. Maximum temperature 325° (163°C). Easy to read digital thermometer.
- Pre-setting automatic controls for cooking and holding cycles allows for unattended operation.
- Cook and hold over 120 lbs. (54 kg.) of meat in just 5 sq. ft. of floor space - per oven.
- Non-venting oven, provides easy, inexpensive installation - no extraction canopy is required.
- Fully insulated, stainless steel interior for ease of cleaning; stainless steel exterior.
- Smooth interior covered corners prevent food particle/grease build up - supplied with removable drip pan.
- Field reversible insulated doors prevent temperature loss. Silicone door gaskets for proper seal. High temperature ceramic magnetic latches for "easy open" and security during transport.
- Safety conscious anti-microbial latches protect against spreading germs.
- Standard with right hand hinges; left hand hinging available upon request.
- 100-CH has Stainless steel pan slides - holds 8 x 18" x 26" (460 x 660mm) pans on 75mm centres per oven. Supplied with 3 wire grids per compartment
- 750-CH has Stainless steel pan slides - holds 5 x 18" x 26" (460 x 660mm) at 35mm centres. Supplied with 3 wire grids
- Heavy duty 5" swivel casters, two with brakes. Provides mobility when fully loaded.

#### OPTIONS:

- 10 pre-set programmes - **£425 per oven**
- Tempered glass door - **£520 per oven**
- Wire shelves (1170 - 005) - **£45**
- 18" x 26" pans - **POA**
- Perimeter bumper - **POA**
- Corner bumpers - **POA**

Fitted with core probe and digital readout



**7 YEAR**  
element  
warranty



Fitted with core probe and digital readout

Model No.	Dimensions	Kw - amps	List Price
<b>1000-CH-SS</b>	575w x 835d x1050h	3 - 13	<b>£5,195</b>
<b>750-CH-SS</b>	655w x 835d x870h	3 - 13	<b>£5,195</b>

Model No.	Dimensions	Kw - amps	List Price
<b>1000-CH-1</b>	575w x 835d x 1950h	6 - 26	<b>£8,895</b>
<b>1000-CH-2</b>	575w x 835d x 1950h	3+3 - 13+13	<b>£9,875</b>

## Counter Top and Under Counter Holding Cabinets

### H339-12-135C Insulated Counter Top Hot Cabinet

Dimensions 445w x 645d x 700h

Power 1kw

#### FEATURES:

- Fitted with easy read digital thermometer
- Fully insulated counter top hot cabinet keeps prepared foods at serving temperatures
- Adjustable humidity vent fitted on door
- Ideal for under counter use also.
- Powerful, yet efficient, 900 Watt heating system maintains the right temperature to properly hold products. Heats up to 200°F (93°C).
- Internal frame in body and door maintains structural rigidity.
- Body constructed of non-corrosive, Hi-Tensile aluminum for strength and ease of mobility.
- Safety-conscious anti-microbial latch protect against spreading germs.
- Insulated field reversible door for flexibility.
- Standard with right hand hinging; left hand hinging available upon request.
- Magnetic latch for "easy open"; Latch and hinges mounted inboard.

- Pan slides securely hold 5 x 1/1GN containers at 70mm centres, removable for easy cleaning.
- Supplied with 3 wire shelves.
- Pan stops on inside of door and back allow for proper air flow.
- Mounted on 4" legs to allow for counter top cleaning.

#### OPTIONS:

- Key lock latches
- Wire shelves - 1/1gn
- Wire shelf (support runners)
- Perimeter bumper
- Corner bumpers
- Stacking kit
- Castors
- Pass thru door



For pricing on these products please contact the office on 01455 55 99 69

£2,220



Fitted with digital temperature read out

### H339-12-188C Insulated Under Counter Hot Cabinet



#### FEATURES:

- Fitted with easy read digital thermometer
- Fully insulated counter top hot cabinet keeps prepared foods at serving temperatures.
- Adjustable humidity vent fitted on door
- Ideal for under counter use also.
- Powerful, yet efficient heating system maintains the right temperature to properly hold products. Heats up to 200°F (93°C).
- Internal frame in body and door maintains structural rigidity.
- Body constructed of non-corrosive, Hi-Tensile aluminum for strength and ease of mobility.
- Safety-conscious anti-microbial latch protect against spreading germs.
- Insulated field reversible door for flexibility.
- Standard with right hand hinging; left hand hinging available upon request.

- Magnetic latch for "easy open" Latch and hinges mounted inboard.
- Wire pan supports will hold either 1/1gn, 400 x 600mm or 18" x 26" (460 x 660mm) pans at 70mm centres which are removable for easy cleaning.
- Supplied with 3 wire shelves - 460 x 660mm.
- Pan stops on inside of door and back allow for proper air flow.
- Fitted with heavy duty 3" castors - two with brakes.



H339-SBS-1210



Fitted with digital temperature read out

Model No.	Finish	Pan Size	Dimensions (mm)	Internal Dimensions	Power	List Price
H339-X12-188C	Aluminium	8 x 460 x 660	705w x 820d x 815h	465w x 670d x 635h	1kw	£2,795
H339-SBS-1210	Aluminium	10 x 1/1gn	940w x 665d x 685h	525w x 545d x 525h	3kw	£2,995

## Half Size Holding Cabinets

### H339-128C Half Size Insulated Hot Cabinet



Fitted with digital temperature read out



#### FEATURES:

- Fitted with easy read digital thermometer
- Fully insulated counter top hot cabinet keeps prepared foods at serving temperatures.
- Adjustable humidity vent fitted on door
- Powerful, yet efficient, 900 Watt heating system maintains the right temperature to properly hold products. Heats up to 200°F (93°C).
- Internal frame in body and door maintains structural rigidity.
- Body constructed of non-corrosive, Hi-Tensile aluminum or 304 stainless steel for strength and ease of mobility. One piece extended base protects cabinet body.
- Safety-conscious anti-microbial latch protect against spreading germs.
- Insulated field reversible door for flexibility. Standard with right hand hinging; left hand hinging available upon request.
- Magnetic latch for "easy open"; twist-lock catch secures door during transport. Latch and hinges mounted inboard.

- Removable wire pan supports for easy cleaning hold 8 x 1/1gn at 70mm centres.
- Supplied with 3 x 1/1gn wire shelves.
- Pan stops on inside of door and back allow for proper air flow.
- Convenient lift handles fold at against sides of cabinet.
- Heavy duty 5" swivel casters, two with brakes. Provides mobility when fully loaded.
- Cabinets can be stacked for flexibility; specify optional stacking kit.

#### OPTIONS:

- Wire shelves - 1/1gn - **£35**
- Perimeter bumper - **POA**
- Corner bumpers - **POA**
- Stacking kit - **POA**
- Pass thru version - **POA**

Model No.	Finish	Pan Size	Dimensions (mm)	Internal Dimensions	List Price
<b>H339-128C</b>	Aluminium	8 x 1/1gn	480w x 695d x 935h	335w x 540d x 635h	<b>£2,790</b>
<b>H339-S128C</b>	Stainless	8 x 1/1gn	480w x 695d x 935h	335w x 540d x 635h	<b>£3,950</b>

### H137... Insulated Hot Cabinet - with humidity

#### FEATURES:

- Fitted with easy read digital thermometer
- Fully insulated hot cabinet keeps prepared foods at serving temperatures.
- Humidity - the Aquatemp system allows you to hold the humidity by adjusting individual thermostats. You can regulate the humidity levels by controlling the air temperature up to a maximum of 82°C
- Powerful, yet efficient, 900 Watt heating system maintains the right temperature to properly hold products. Heats up to 200°F (93°C).
- Internal frame in body and door maintains structural rigidity.
- Body constructed of 304 stainless steel for strength and ease of mobility. One piece extended base protects cabinet body.
- Safety-conscious anti-microbial latch protect against spreading germs.
- Insulated field reversible door for flexibility. Standard with right hand hinging; left hand hinging available upon request.

- Magnetic latch for "easy open"; twist-lock catch secures door during transport. Latch and hinges mounted inboard.
- Wire pan supports will hold 2/1gn containers at 110mm centres or 18" x 26" pans at 110mm centres which are removable for easy cleaning - Supplied with 2 wire shelves
- Pan stops on inside of door and back allow for proper air flow.
- Convenient lift handles fold at against sides of cabinet.
- Heavy duty 5" swivel casters, two with brakes. Provides mobility when fully loaded.
- Cabinets can be stacked for flexibility; specify optional stacking kit.

#### OPTIONS:

- Wire shelves - **£35**
- Perimeter bumper - **POA**
- Corner bumpers - **POA**
- Stacking kit - **POA**
- Pass thru version - **POA**

Fitted with digital temperature read out



Model No.	Finish	Pan Capacity	Dimensions (mm)	Internal Dimensions	List Price
<b>H137-WSUA5</b>	Stainless	5	715w x 895d x 815h	540w x 700d x 510h	<b>£4,530</b>
<b>H137-WSUA6</b>	Stainless	6	715w x 895d x 1095h	540w x 700d x 790h	<b>£4,770</b>

## Full Size Holding Cabinets

### H137 Insulated Hot Cabinet - with or without humidity

#### FEATURES:

- Fitted with easy read digital thermometer
- Fully insulated hot cabinet keeps prepared foods at serving temperatures
- Humidity - the Aquatemp system allows you to hold the humidity by adjusting individual thermostats. You can regulate the humidity levels by controlling the air temperature up to a maximum of 82°C
- Powerful, yet efficient, 1500 Watt heating system maintains the right temperature to properly hold products. Heats up to 200°F (93°C)
- Self-contained power top allows interior of cabinet to be hosed-out during cleaning
- Internal frame in body maintains structural rigidity
- 304 stainless steel construction throughout for ease of cleaning
- One piece extended base protects cabinet body
- Smooth interior coved corners prevent food particle/grease buildup
- Safety-conscious anti-microbial latches protect against spreading germs
- Field reversible insulated Dutch doors prevent temperature loss
- Silicone door gaskets for proper seal
- Standard with right hand hinging; left hand hinging available upon request
- High temperature ceramic magnetic latches for "easy open"; twist-lock catch secures door during transport
- Latches and hinges mounted inboard
- Recessed push/pull handles on both sides prevents damage to walls; allows easy maneuvering
- 12 sets of wire pan supports will hold 12 x 2/1qn containers at 110mm centres or 18" x 26" pans at 110mm centres which are removable for easy cleaning - Supplied with 8 wire shelves
- Heavy duty 5" swivel casters, two with brakes. Provides mobility when fully loaded

#### OPTIONS - PLEASE RING THE OFFICE:

- Tempered glass door
- Key lock latches
- Wire shelves
- Wire shelf (support runners)
- 18" x 26" pans
- 2/1qn containers
- Perimeter bumper
- Corner bumpers
- Floor lock for 5" castors
- Push handles



Model No.	Finish	Pan Size	Dimensions (mm)	Internal Dimensions	Power	Weight	List Price
H137-UA-12C	Aluminium	12x2/1qn	730w x 870d x 1855h	560w x 700d x 1475h	2kw	100kg	<b>£4,850</b>
H137-SUA-12C	Stainless	12x2/1qn	730w x 870d x 1855h	560w x 700d x 1475h	2kw	128kg	<b>£6,150</b>
H137-WSUA-12C (with humidity)	Stainless	12x2/1qn	730w x 870d x 1855h	560w x 700d x 1475h	2kw	130kg	<b>£6,765</b>

## Pass thru' Full Size Holding Cabinets



### H137-PS Pass thru' - Insulated hot cabinet - with or without humidity

#### FEATURES:

- Fitted with easy read digital thermometer
- Fully insulated hot cabinet keeps prepared foods at serving temperatures
- Humidity - the Aquatemp system allows you to hold the humidity by adjusting individual thermostats. You can regulate the humidity levels by controlling the air temperature up to a maximum of 82°C
- Powerful, yet efficient, 1500 Watt heating system maintains the right temperature to properly hold products. Heats up to 200°F (93°C).
- Self-contained power top allows interior of cabinet to be hosed-out during cleaning.
- Internal frame in body maintains structural rigidity.
- 304 stainless steel throughout for ease of cleaning.
- One piece extended base protects cabinet body.
- Smooth interior coved corners prevent food particle/grease buildup.
- Safety-conscious anti-microbial latches protect against spreading germs.
- Field reversible insulated Dutch doors prevent temperature loss.
- Silicone door gaskets for proper seal.
- Standard with right hand hinging; left hand hinging available upon request.
- High temperature ceramic magnetic latches for "easy open"; twist-lock catch secures door during transport.
- Latches and hinges mounted inboard.
- Recessed push/pull handles on both sides prevents damage to walls; allows easy maneuvering.
- 12 sets of wire pan supports will hold 12 x 2/1qn containers at 110mm centres or 18" x 26" pans at 110mm centres which are removable for easy cleaning - Supplied with 8 wire shelves.
- Heavy duty 5" swivel casters, two with brakes. Provides mobility when fully loaded.

#### OPTIONS - PLEASE RING THE OFFICE:

- Tempered glass door
- Key lock latches
- Wire shelves
- Wire shelf (support runners)
- 18" x 26" pans
- 2/1qn containers
- Perimeter bumper
- Corner bumpers
- Floor lock for 5" castors
- Push handles

Model No.	Finish	Pan Size	Dimensions (mm)	Internal Dimensions	Power	Weight	List Price
<b>H137-PSUA-12C</b>	Stainless	12 x 2/1qn	730w x 870d x 1855h	560w x 700d x 1475h	2kw	128kg	<b>£6,970</b>
<b>H137-WPSUA-12C</b> (with humidity)	Stainless	12 x 2/1qn	730w x 870d x 1855h	560w x 700d x 1475h	2kw	128kg	<b>£7,585</b>